


# ゴム丸ヒモ



## シリコン (Si)

・硬度50~60° 原色

直径 φ	長さ
1.0	100 m
1.5	
2.0	
2.5	
3.0	
3.5	
4.0	
5.0	
5.3	
5.7	
6.0	
6.4	
7.0	
8.0	
8.4	
9.0	50 m
10.0	
12.0	
15.0	
16.0	
20.0	
25.0	
30.0	20 m

## クDDブレン / ネオブレン (CR)

・硬度60~65°

直径 φ	長さ
1.5	100 m
2.0	
2.5	
3.0	
3.5	
4.0	
5.0	
5.7	20 m
6.0	25 m
7.0	
8.0	20 m
8.4	12 m
9.0	50 m
10.0	
11.0	
12.0	
13.0	
14.0	
15.0	
16.0	
17.0	
18.0	30 m
19.0	40 m
20.0	
25.0	25 m
30.0	

## ニトリル (NBR)

・硬度65°

直径 φ	長さ
2.0	100 m
2.5	
3.0	
3.5	
4.0	
5.0	50 m
5.7	
6.0	
7.0	
8.0	
8.4	
9.0	
10.0	30 m
11.0	
12.0	40 m
13.0	
14.0	25 m
15.0	
16.0	
17.0	
18.0	
19.0	20 m
20.0	
25.0	
30.0	

## フッ素 (FKM)

・硬度70°

直径 φ	長さ
2.0	100 m
2.5	
3.0	
3.5	
4.0	
5.0	
5.3	
5.7	
6.0	
6.4	
7.0	50 m
8.0	
8.4	
9.0	
10.0	
11.0	
12.0	
15.0	

※ 任意の長さでカット加工や追加加工あるいは少量対応が可能です。