


押し製品

スクリー式押し機から、ところてんのように、生ゴムを圧力で口金と呼ぶノズルより押し出し、オープンや蒸気等で、ゴム製品とする製作方式です。

又、材質、寸法、形状、硬度、色等も特殊仕様で製作できるものもありますので、お問い合わせください。

1. ゴムチューブ



シリコン (Si)

- ・硬度50～60°
- ・使用温度 -60℃～200℃
- ・耐老化、耐オゾン、その他物理的性質に優れる

内径 φ	外径 φ	長さ		
0.5	1.0			
1.0	1.5	100 m		
	2.0			
	3.0			
1.0	5.0			
1.15	3.0			
1.5	2.5		50 m	
	3.0			
	4.0			
2.0	3.0			100 m
	3.5			
	4.0			
	6.0			
	8.0			
2.5	4.0	50 m		
	5.0			
3.0	5.0		20 m	
	6.0			
	9.0			
4.0	6.0			50 m
	7.0			
	8.0			
	9.0			
5.0	10.0			
	7.0			
	8.0			
	9.0			
6.0	10.0	50 m		
	11.0			
	8.0			
	9.0			
7.0	10.0		50 m	
	12.0			
	15.0			
	10.0			

内径 φ	外径 φ	長さ		
7.0	11.0	50 m		
	12.0			
	13.0			
8.0	10.0		50 m	
	11.0			
	12.0			
9.0	14.0			30 m
	12.0			
	13.0			
10.0	15.0			
	13.0			
	14.0			
12.0	16.0	20 m		
	18.0			
	15.0			
	20.0			
15.0	20.0		20 m	
	24.0			
	18.0			
	25.0			
20.0	28.0			20 m
	32.0			
	25.0			
	33.0			
32.0	42.0	20 m		
	38.0			
	32.0			
	48.0			

クDDDプレ / ネオプレン (CR)

- ・硬度50～60°

内径 φ	外径 φ	長さ			
2.0	4.0	100 m			
	5.0				
3.0	6.0		50 m		
	7.0				
	8.0				
4.0	10.0			100 m	
	7.0				
	8.0				
5.0	9.0				50 m
	10.0				
	14.0				
	15.0				
	8.0				
6.0	9.0	50 m			
	10.0				
	12.0				
	14.0				
7.0	15.0		30 m		
	10.0				
	13.0				
	12.0				
8.0	13.0			50 m	
	14.0				
	15.0				
9.0	13.0	30 m			
	14.0				
10.0	14.0				50 m
	16.0				
12.0	18.0		30 m		
	15.0				
	17.0				
15.0	20.0			35 m	
	18.0				
18.0	24.0				
	25.0				
25.0	33.0	20 m			
	33.0				

ニトリル (NBR)

- ・硬度50～60°

内径 φ	外径 φ	長さ				
3.0	5.0	50 m				
	7.0					
4.0	6.0		30 m			
	7.0					
5.0	9.0			20 m		
	12.0					
6.0	9.0				20 m	
	12.0					
7.0	10.0					20 m
	11.0					
	12.0					
8.0	14.0	20 m				
	16.0					
	20.0					
18.0	24.0		20 m			
	33.0					

フッ素 (FKM)

- ・硬度70°

内径 φ	外径 φ	長さ				
1.0	3.0	100 m				
	4.0					
3.0	5.0		50 m			
	6.0					
4.0	7.0			30 m		
	8.0					
5.0	8.0				30 m	
	8.5					
6.0	9.0					50 m
	10.0					
	11.0					
7.0	12.0	30 m				
	13.0					
8.0	13.0		20 m			
	14.0					
9.0	16.0			20 m		
	17.0					
	20.0					
	23.0					

※ 任意の長さでカット加工や追加加工あるいは少量対応が可能です。